

Amendments to the Claims:

This listing of the claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) Wall with a set of doors for closing off a bay (3) in this wall (4), comprising
a first flexible door (1) and a second door (2) having at least a rigid bottom edge (17), each of these doors being movable between an open position and a closed position through, respectively, an upward movement and a downward movement,
a slit (31) being provided between the wall (4) and the rigid bottom edge (17) of the second door (2) as this second door is moved upwards into the open position,
the flexible door (1) at least partially being arranged between said second door (2) and said wall (4),
wherein when the second door (2) is in the open position
- the flexible door (1) is movable through the slit (3) between the open position and the closed position of the flexible door,
Wherein when the second door (2) is in the open position and the flexible door (1) is in its closed position

- the flexible door (1) is in contact with the wall (4) above the bay (3) to form a seal between the wall (4) and the flexible door (1), and

- the flexible door (1) is supported against the bottom edge (17) of the second door (2) in order to maintain said contact and seal.

2. (Cancelled).

3. (Currently Amended) Wall with a set of doors as claimed in ~~claims~~ claim 1, wherein the flexible door (1) has a sealing element (26) fixed thereto and extending across substantially the entire width of the flexible door (1), which sealing element extends between this door (1) and a part of the wall (4) located above the bay (3), the sealing element forming a seal between the wall (4) and the flexible door (1) when the flexible door (1) is in the closed position.

4. (Currently Amended) Wall with a set of doors as claimed in claim 1, wherein the flexible door has a sealing element (26) fixed thereto and extending along substantially the entire width of the flexible door (1) which extends between this door (1) and the bottom edge (17) of the second door (2) so that the flexible door (1) is clamped between the wall (4) and this

bottom edge (17) when the flexible door is in the closed position.

5. (Cancelled).

6. (Currently Amended) Wall with a set of doors as claimed in claim 3, wherein the sealing element (26), which is fixed to the flexible door, is a thickened section (28) of an elastic material, the sealing element being clamped between the wall (4) and the bottom edge (17) of the second door (2) when the second door is in the open position and when said flexible door (1) is in its closed position.

7. (Previously Presented) Wall with a set of doors as claimed in claim 1, wherein, when said second door (2) is in the open position, as said flexible door (1) is displaced towards its closed position or towards its open position, the flexible door is supported against a guide surface on the wall (4) above the bay (3) or on the bottom edge (17) of the second door (2).

8. (Previously Presented) Wall with a set of doors as claimed in claim 7, characterised in that the bottom edge (17) of the second door (2) is provided with said guide surface

(25), such that the flexible door slides on this edge (17) as the flexible door is moved upwards or downwards.

9. **(Previously Presented)** Wall with a set of doors as claimed in claims 7 or 8, wherein a part of the wall (4) located above the bay (3) has said guide surface (25) such that the flexible door (1) slides relative to this wall (4) as it is moved upwards or downwards.

10. **(Previously Presented)** Wall with a set of doors as claimed in claim 8, wherein the guide surface comprises at least one cylinder (25) with an axis which extends substantially transversely to the direction of displacement of the flexible door (1) as it is moved downwards or upwards.

11. **(Previously Presented)** Wall with a set of doors as claimed in claim 1, wherein the flexible door (1) comprises a shutter (9) with side edges (7, 8) that are guided relative to guide tracks (5, 6) passing through said slit between the wall (4) and the bottom edge (17) of the second door (2).

12. **(Previously Presented)** Wall with a set of doors as claimed in claim 11, wherein said guide tracks (5, 6) extend at least partially in the bay (3) or at the side of the bay that is directed towards the second door (2).

13. **(Previously Presented)** Wall with a set of doors as claimed in claim 11 or 12, characterised in that the guide tracks (5, 6) are elastically or pivotably mounted to the wall (4).

14. **(Previously Presented)** Wall with a set of doors for closing off a bay (3) in this wall (4), comprising

a first flexible door (1) and a second door (2) having at least a rigid bottom edge (17), each of these doors being movable between an open position and a closed position through, respectively, an upward movement and a downward movement,

a slit (31) being provided between the wall (4) and the rigid bottom edge (17) of the second door (2) as this second door is moved upwards into the open position, the flexible door (1) at least partially being arranged between said second door (2) and said wall (4),

wherein the flexible door (1) is movable through the slit (3) between the open position and the closed position of the flexible door when the second door (2) is in the open position,

wherein the flexible door is supported against the bottom edge (17) of the second door (2) when this second door

(2) is in the open position and the flexible door (1) is in its closed position,

wherein the flexible door (1) comprises a shutter (9) with side edges (7, 8) that are guided relative to guide tracks (5, 6) passing through said slit between the wall (4) and the bottom edge (17) of the second door (2),

wherein the guide tracks (5, 6) constitute seals between the wall (4) and said second door (2) when the latter is in the closed position.

15. **(Previously Presented)** Wall with a set of doors for closing off a bay (3) in this wall (4), comprising

a first flexible door (1) and a second door (2) having at least a rigid bottom edge (17), each of these doors being movable between an open position and a closed position through, respectively, an upward movement and a downward movement,

a slit (31) being provided between the wall (4) and the rigid bottom edge (17) of the second door (2) as this second door is moved upwards into the open position,

the flexible door (1) at least partially being arranged between said second door (2) and said wall (4),

wherein the flexible door (1) is movable through the slit (3) between the open position and the closed position of

the flexible door when the second door (2) is in the open position,

wherein the bottom edge (16) of the flexible door (1) has an elastic bead extending across its entire width, ~~which is~~ said elastic head being clamped between the wall (4) and the second door (2) when the flexible door (1) is in its open position and the second door (2) is in its closed position.

16. **(Previously Presented)** Wall with a set of doors as claimed in claim 15, wherein a guide surface (25) is provided on the bottom edge (17) of the second door (2) whereby the flexible door (2) slides on this bottom edge (17) as it is moved upwards or downwards.

17. **(Previously Presented)** Wall with a set of doors as claimed in claims 15 or 16, wherein a guide surface (25) is provided on the wall (4) above the bay (3) enabling the flexible door (1) to slide relative to this wall (4) as it is moved upwards or downwards.

18-25. **(Cancelled)**.